

PRODUCT DATASHEET

Surface mounted Panel light HYD-122CR-15W 6500K



Application

- Office
- Kitchen
- Rest room
- Corridor
- Shop

Benefits

- The light is soft and bright
- Drive stable, safe and reliable
- High light transmission mask to ensure uniform light

Features

- Efficient and durable
- Easy and quick installation
- Light body thin design, reduce space occupancy
- Die-cast aluminum body for better heat dissipation, anti-corrosion, and easy maintain





Electrical Data

Nominal wattage (W)	15W
Nominal Voltage (V)	100-240
Mains Frequency (Hz)	50
Nominal Current (mA)	72
LED Driver Current (mA)	400
LED Driver Voltage (V)	30-40
LED Driver Efficiency (%)	
Power Factor λ	0.9
Total harmonic distortion (%)	
Operating mode	External LED driver

Photometrical data

Luminous flux ±10% (lm)	1678 lm	
Luminous efficacy	108 lm/w	
Color temperature	6500K	
Light color (designation)	Cold White	
Color rendering index Ra	≥80	
Standard deviation of color matching	≤5 SDCM	
Luminous intensity/cd	508	
Flickering	Flicker	
Beam angle	119 °	






IES



Dimensions & Weight

Diameter (mm)	175
Height (mm)	50
Product weight (g)	422



Material & Colors

Product color	All White	
Housing color	White	
Body material	Aluminum	
Cover material	PC	
Mercury content	0.0 mg	

Application & Mounting

Ambient temperature range	-20-45 °C		
Temperature range at storage	-25-60 °C		
Type of connection	Screw terminal		
Type of protection	IP20		
Dimmable	175*50 mm		
Mounting type	Surface mounted		
Mounting location	Ceiling		
Application environment	Indoor		
Cut size (mm)	No		
LED module replaceable	Not replaceable		
With light source	Yes		




Certificates & Lifespan


Life (h)	50,000		
Certificates	CB / ENEC /RoHS		
Standards	ISO9001:2015		


Logistical Data


Product code	Dimensions	Pcs/	G.W.	Volume
	(L*W*H)	carton	kg	CBM
HYD-122CR-15W	38*31*38.5 cm	20	•••	0.04535

Installation Method









Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release